

2045 Montreux Plus


May 28, 2010



ZipperLock® Technology

Real world experience shows that high tuft bind alone is not sufficient to prevent zippering. ZipperLock® Technology includes the following:

- Dual Bonding provides excellent lamination strength and tuft bind
- Interlocking Tuft Placement prevents unraveling




Stain Proof - No Exceptions™

Strudon® is inherently stain proof. Carpets made of Strudon® fiber are ideal for high stain environments including food service areas and rental units.




Scoured & Extracted™ to Stay Clean Longer

This solution dyed carpet is Scoured & Extracted™ to remove the processing oils that attract soil. Scouring makes the carpet easier to clean, and helps prevent accelerated soiling known as Rapid Resoil.



Kraus® Endorsed Recycling Program

This product is eligible for a recycling program. 100% of this carpet is recyclable.



10 Year Warranties

- Commercial wear
- ZipperLock® + no edge ravel + no delamination
- Stain Proof – No Exceptions™
- Anti-Shock

See full text for details.

Style 2045

02 Camel
30 Sand Dune

03 Black Pepper
37 Acorn

06 Dust Storm
39 Coal

07 Sea Breeze
48 Fir

April 28, 2011

Style 2045 Montreux Plus
Manufacturer Kraus® Inc.

CONSTRUCTION

Fiber system	92% BCF Strudon® / 8% BCF nylon	
Construction	Interlocking level loop	
Standard backing system	ZipperLock® dual bonding	
Pile weight	20 oz/y ²	678 g/m ²
Pile height	0.18"	4.5 mm
Gauge	1/10	39.4 rows/10 cm
Stitches	9.7 s.p.i.	38.2 stitches/10 cm
Density	4500	8.7 kilotex/cm ²

PROTECTION

Coloration	Solution dyed / yarn dyed
Stain resistance	Stain Proof - No Exceptions™
Soil protection	Scoured & Extracted™

SUSTAINABILITY

CRI/CCI air quality test	Green Label Plus	GLP 4678
Recycling program	Eligible for recycling program	

PERFORMANCE

Ravel test performance	Construction prevents raveling when tested to PTL-CR (center ravel) and PTL-ER (edge ravel) protocols	
Static generation	Maximum 3.0 kV (AATCC 134)	
Flammability	Canada: CGSB 4GP-129 CAN 4-S102.2 (generic per NBC supplement)	
Light fastness	USA: Radiant Panel ASTM E648 – Class II	
Change on wet cleaning	L5 Gray scale 5	

INSTALLATION

Approximate pattern repeat (w x l)	5/8" x 1 1/4"	1.6 cm x 2.8 cm
Installation method	Suitable for direct glue or cushion installations	
Chair protectors	Recommended for direct glue installations Mandatory for cushion installations	

WARRANTIES

10 year Warranties (See full text for details)	Commercial wear ZipperLock® + no edge ravel Stain Proof – No Exceptions™ Anti-shock
---	--

Follow manufacturer's installation recommendations. Correct seam sealing is necessary to prevent seam breakdowns. For best results, seams must be row cut and the carpet must be dry laid to optimize pattern match. Due to dye lot variations, actual material may vary slightly from samples. The manufacturer reserves the right to modify the specifications to improve the product without notice and without prejudice. See krausflooring.com for latest specifications.

E&OE.





LEED Specifications

Style Name: Montreux Plus (broadloom)

MR 2.1 and MR 2.2

Construction Waste Management:

Recycle used broadloom in Kraus' carpet reclamation program

Contributes to up to 2 LEED points

MR 5.1

Regional Materials

Kraus products are manufactured in Waterloo, Ontario

Contributes to 1 LEED point

EQ 4.1

Low Emitting Materials: Adhesives

Kraus products are compatible with low VOC adhesives

Contributes to 1 LEED point

EQ 4.2

Low Emitting Materials: Carpet

This product meets the requirements of the Carpet & Rug Institute's Green Label Plus Indoor Air Quality Testing Program

1 LEED point

65 Northfield Drive West
Waterloo, Ontario
Canada N2J 4J4

tel 519.884.2310
fax 519.884.0170